



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A62D 1/08	A1	(11) International Publication Number: WO 91/12853 (43) International Publication Date: 5 September 1991 (05.09.91)
(21) International Application Number: PCT/US91/00999 (22) International Filing Date: 14 February 1991 (14.02.91) (30) Priority data: 488,295 2 March 1990 (02.03.90) US (71) Applicant: GREAT LAKES CHEMICAL CORPORATION [US/US]; Post Office Box 2200, Highway 52 Northwest, West Lafayette, IN 47906 (US). (72) Inventor: ROBIN, Mark, L. ; 5411 Hillside Lane, West Lafayette, IN 47906 (US). (74) Agents: HENRY, Thomas, Q. et al.; Woodard, Emhardt, Naughton, Moriarty & McNett, Bank One Center/Tower, 111 Monument Circle, Suite 3700, Indianapolis, IN 46204-5137 (US).		(81) Designated States: AT (European patent), AU, BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), NL (European patent), SE (European patent), SU. Published <i>With international search report.</i>
(54) Title: FIRE EXTINGUISHING METHODS AND COMPOSITIONS UTILIZING 2-CHLORO-1,1,1,2-TETRAFLUOROETHANE (57) Abstract Methods for extinguishing fires are disclosed which include the use of 2-chloro-1,1,1,2-tetrafluoroethane as a fire extinguishing agent. The 2-chloro-1,1,1,2-tetrafluoroethane may be used alone or in combination with other halogenated hydrocarbon fire extinguishants. Compositions including the 2-chloro-1,1,1,2-tetrafluoroethane and other extinguishants are also disclosed. The compositions are effective at low concentrations and are non-toxic and environmentally safe.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

-1-

FIRE EXTINGUISHING METHODS AND COMPOSITIONS
UTILIZING 2-CHLORO-1,1,1,2-TETRAFLUOROETHANE

BACKGROUND OF THE INVENTION

5

Field of the Invention:

The present invention relates to the field of fire extinguishing compositions and methods using halogenated hydrocarbons.

10

Description of the Prior Art:

The use of certain halogenated chemical agents for the extinguishment of fires is common. These agents are thought to be effective due to their interference with the normal chain reactions responsible for flame propagation. The most widely accepted mechanism for flame suppression is the radical trap mechanism proposed by Fryburg in Review of Literature Pertinent to Fire Extinguishing Agents and to Basic Mechanisms Involved in Their Action, NACA-TN 2102 (1950). It is generally accepted that compounds containing the halogens Cl, Br and I act by interfering with free radical or ionic species in the flame, and that the effectiveness of these halogens is in the order I>Br>Cl. The presence of fluorine has not been considered as contributing to the fire extinguishing properties of a compound, but will impart stability, reduce toxicity and boiling point, and increase thermal stability.

25

Various halogenated hydrocarbons have been used or proposed for use as fire extinguishants. Prior to 1945, three halogenated fire extinguishing agents widely used

30

-2-

were carbon tetrachloride (Halon 104), methyl bromide (Halon 1001) and chlorobromomethane (Halon 1011). For toxicological reasons, however, the use of these agents has been discontinued. The three fire extinguishing agents presently in common use are bromine-containing compounds, Halon 1301 (CF_3Br), Halon 1211 (CF_2BrCl) and Halon 2402 ($\text{CF}_2\text{BrCF}_2\text{Br}$). The effectiveness of these three volatile, bromine-containing compounds in extinguishing fires has been described in United States Patent No. 4,014,799, issued to Owens. In addition, the use of dibromodifluoromethane, Halon 1202 (CF_2Br_2), has been reported, although the compound is highly toxic. The NFPA publication, the Fire Protection Handbook, Section 18, Chapter 2, entitled "Halogenated Agents and Systems" (1985) describes these agents in more detail.

Although the above named bromine-containing Halons are effective fire fighting agents, those agents containing bromine or chlorine are asserted by some to be capable of the destruction of the earth's protective ozone layer. For example, Halon 1301 has an Ozone Depletion Potential (ODP) rating of 14.26, and Halon 1211 has an ODP of 2.64. Also, because the agents contain no hydrogen atoms which would permit their destruction in the troposphere, the agents may also contribute to the greenhouse warming effect.

Although not employed commercially, certain chlorine-containing compounds are also known to be effective extinguishing agents, for example Halon 251 ($\text{CF}_3\text{CF}_2\text{Cl}$), as described by Larsen in United States

-3-

Patent No. 3,844,354. The use of trichlorofluoromethane (CFCl_3) with all or any of dichlorodifluoromethane (CCl_2F_2), trichlorotrifluoroethane ($\text{CCl}_2\text{F}-\text{CClF}_2$) or dichlorotetrafluoroethane ($\text{CClF}_2-\text{CClF}_2$) in fire
5 extinguishers is disclosed in United States Patent No. 4,826,610, issued to Thacker on May 2, 1989. In United States Patent No. 3,733,273, issued to Munro on May 15, 1973, it is disclosed that an azeotropic mixture of 1,2-dichloro-1,1,2,2-tetrafluoroethane and
10 1-chloro-1,2,2-trifluoroethane is useful as a fire extinguishing agent. Various other halogenated fire extinguishing agents have been disclosed in the prior art, including in United States Patent Nos. 4,606,832, issued to Hisamoto et al. on August 19, 1986;
15 3,879,297, issued to Languille et al. on April 22, 1975; 3,822,207, issued to Howard et al. on July 2, 1974; 3,080,430, issued to Cohen on March 5, 1963; and, 4,226,728, issued to Kung on October 7, 1980.

Several factors enter into the selection and use of
20 halogenated hydrocarbons as fire extinguishants. As already mentioned, brominated hydrocarbons in particular present concerns with ozone depletion. Compounds which do not include bromine tend to be ineffective at safe levels, or toxic at effective levels. It has therefore
25 remained desirable to provide fire extinguishants which satisfy the various criteria applicable for use of these compounds. In particular, there continues to be a need for fire extinguishing agents which are effective and non-toxic, and which have low ozone depletion ratings
30 and minimal impact on the greenhouse warming effect.

-4-

The present invention involves the use of 2-Chloro-1,1,1,2-tetrafluoroethane as a fire extinguishant, either alone or in combination with other compounds. This compound is commonly known as Freon 124. Applicant
5 has discovered that this compound has surprising efficacy at safe concentrations. Although the compound is well known, it has not been proposed for use as a fire extinguishant. Instead, Freon 124 has only been indicated in the past as being useful as a propellant or
10 refrigerant.

SUMMARY OF THE INVENTION

Briefly describing one aspect of the present invention, there is provided a method for extinguishing a fire which comprises introducing to the fire a fire
15 extinguishing concentration of an extinguishant composition including 2-Chloro-1,1,1,2-tetrafluoroethane, and maintaining the concentration of the composition until the fire is extinguished. The 2-Chloro-1,1,1,2-tetrafluoroethane
20 may be used alone, or in combination with other halogenated hydrocarbon fire extinguishants. Blends of 2-Chloro-1,1,1,2-tetrafluoroethane with such other extinguishants are also contemplated.

It is an object of the present invention to provide
25 an effective method for extinguishing fires.

Another object of the present invention is to provide a fire extinguishing method which utilizes particular halogenated hydrocarbons, including specifically 2-Chloro-1,1,1,2-tetrafluoroethane, which
30 are effective at non-toxic and non-anesthetic levels.

-5-

It is a further object of the present invention to provide a fire extinguishing method which employs compounds that are environmentally safe, having low ozone depletion potential and greenhouse warming effect.

5 A further object of the present invention is to provide fire extinguishing compositions comprising blends of 2-Chloro-1,1,1,2-tetrafluoroethane and other halogenated hydrocarbons, which blends are effective and safe in use.

10 Further objects of the present invention will be apparent from the description which follows.

DESCRIPTION OF THE PREFERRED EMBODIMENT

For the purposes of promoting an understanding of the principles of the invention, reference will now be made to preferred embodiments of the invention and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended, such alterations, further modifications and applications of the principles of the invention as described herein being contemplated as would normally occur to one skilled in the art to which the invention relates.

The present invention provides methods and compositions which are useful for extinguishing fires, and which particularly are safe and effective in use. In one aspect, the invention relates to methods for fire extinguishing which are improved by using 2-Chloro-1,1,1,2-tetrafluoroethane, alone or in a blend, as the fire extinguishing agent. The 2-Chloro-1,1,1,2-tetrafluoroethane is environmentally safe and is

non-toxic and non-anesthetic at effective levels. The invention also relates to the provision of fire extinguishing compositions comprising blends of 2-Chloro-1,1,1,2-tetrafluoroethane with other halogenated hydrocarbon fire extinguishants.

2-Chloro-1,1,1,2-tetrafluoroethane (CF_3CHFCl) is a halogenated hydrocarbon commonly known as Freon 124. It has a molecular weight of 136.48 and a boiling point of -12°C . Prior to this invention, Freon 124 has been used as a propellant or refrigerant, and its use in these regards is described in numerous prior art publications, including United States Patent Nos. 4,224,795, 4,172,043, and 4,072,027.

Methods for the preparation of 2-Chloro-1,1,1,2-tetrafluoroethane are known in the prior art. For example, 2-Chloro-1,1,1,2-tetrafluoroethane may be prepared by fluorination of $\text{CCl}_2=\text{CCl}_2$ with HF, as described in European Patent Application No. 313,061 (1989). An alternative preparation is by reaction of $\text{CF}_2=\text{CFCl}$ with KF/formamide, as reported in the Journal of the American Chemical Society, vol. 82, p. 3091 (1960).

In accordance with one embodiment of the present invention, there is provided a method for extinguishing fires which includes the use of 2-Chloro-1,1,1,2-tetrafluoroethane as a fire extinguishing agent. The 2-Chloro-1,1,1,2-tetrafluoroethane may be applied in the variety of ways employed for other halogenated hydrocarbons, including application in flooding systems, portable

-7-

systems and specialized systems, described hereafter in more detail. 2-Chloro-1,1,1,2-tetrafluoroethane is effective in low concentrations, and of course at high concentrations as well. The concentration employed may depend to some extent on the nature of the fire, the combust-
6 ing material and the circumstances of application. Generally, application rates of 2-Chloro-1,1,1,2-tetrafluoroethane alone preferably range from about 1% to about 15% v/v, and more
10 preferably between about 3% and about 10% v/v.

A particular consideration in selecting a concentration for the 2-Chloro-1,1,1,2-tetrafluoroethane is the maintenance of the area in a non-toxic and non-anesthetic condition. A 50% lethal dose (LD 50) for
15 a compound is that concentration of the compound (volume of compound per volume of air) at which 50% of a test population is killed; a 50% anesthetic dose (AD 50) is that concentration at which 50% of a test population is anesthetized. 2-Chloro-1,1,1,2-tetrafluoroethane has an
20 LD50 of 44.7% v/v, and an AD50 of 15.5% v/v, as reported by Davies, et al., Int. J. Quantum Chem: Quantum Biology Symp No. 3, 171 (1976). Selection of the appropriate usage rate will be affected by these properties. For example, a usage rate where humans may be present is
25 below about 15% v/v, and more preferably below about 10% v/v.

A further desirable aspect of the present invention is that 2-Chloro-1,1,1,2-tetrafluoroethane is environmentally safer than many of the prior art
30 halogenated hydrocarbon fire extinguishants.

-8-

2-Chloro-1,1,1,2-tetrafluoroethane has an ODP of 0.018, as compared to an ODP of 14.26 for Halon 1301 and of 2.64 for Halon 1211, two common commercial fire extinguishants. It is believed that the presence of the hydrogen in 2-Chloro-1,1,1,2-tetrafluoroethane makes the compound less stable and contributes to the lower ODP, since the molecules are susceptible to breakdown in the lower atmosphere. It will be appreciated that the substitution of 2-Chloro-1,1,1,2-tetrafluoroethane for prior art compounds having a higher ODP will greatly reduce the ozone depletion potential of the overall composition.

It is also an aspect of the present invention that 2-Chloro-1,1,1,2-tetrafluoroethane may be employed with other extinguishants to provide a blend having improved characteristics in terms of efficacy, toxicity and/or environmental safety. As previously reported, various halogenated hydrocarbons have been used or proposed in the prior art for use as fire extinguishants. These extinguishants include bromodifluoromethane (CHF_2Br - Halon 1201), dibromodifluoromethane (CF_2Br_2 - Halon 1202), bromotrifluoromethane (CF_3Br - Halon 1301), bromochlorodifluoromethane (CF_2BrCl - Halon 1211), chloropentafluoroethane ($\text{CF}_3\text{CF}_2\text{Cl}$ - Halon 251), dibromotetrafluoroethane ($\text{CF}_2\text{BrCF}_2\text{Br}$ - Halon 2402), bromotetrafluoroethane (CF_3CHFBr), and mixtures thereof. 2-Chloro-1,1,1,2-tetrafluoroethane may be combined, preferably in an amount of from about 1% to about 99%, with one or more of these extinguishants and employed in a method for extinguishing fires.

-9-

As will be seen from the examples which follow, the mixtures of 2-Chloro-1,1,1,2-tetrafluoroethane with bromodifluoromethane are especially attractive due to their low ODP. Also, the similarity of boiling points for the two compounds allows the composition discharged or otherwise applied to remain essentially constant. Blends having from about 5% to about 99% Freon 124 and from about 95% to about 1% bromodifluoromethane are particularly preferred.

One of the surprising and advantageous aspects of the present invention is that the 2-Chloro-1,1,1,2-tetrafluoroethane has been found to be effective at low concentrations, even though the compound does not include bromine. By contrast, it has previously been considered that the most effective halogenated fire extinguishants have been limited to those which contain bromine, and which are fully halogenated. It has also recently been discovered by applicant and a co-worker that heptafluoropropane ($\text{CF}_3\text{CHF}\text{CF}_3$), 1,1,1,3,3,3-Hexafluoropropane ($\text{CF}_3\text{CH}_2\text{CF}_3$), 1,1,1,2,3,3-Hexafluoropropane ($\text{CF}_3\text{CHFCHF}_2$) and pentafluoroethane (CF_3CHF_2) are useful fire extinguishants, as disclosed in co-pending United States Patent Application, Serial No. 439,738, filed on November 21, 1989. 2-Chloro-1,1,1,2-tetrafluoroethane has been determined to be effective in blends with these four compounds.

As demonstrated in the subsequent examples, mixtures of 2-Chloro-1,1,1,2-tetrafluoroethane with $\text{CF}_3\text{CHF}\text{CF}_3$ are especially valuable. The mixtures have ultra low

-10-

ODP and exhibit a large synergistic effect. Such mixtures extinguish a flame at total percent of agents in air less than that of either agent when used alone. Also, the total weight of mixtures to extinguish is less than that of either agent when used alone. Blends, having from about 5% to about 99% Freon 124 and from about 95% to about 1% $\text{CF}_3\text{CHF}\text{CF}_3$ are particularly preferred.

The relative amounts of the 2-Chloro-1,1,1,2-tetrafluoroethane and other compounds is not critical, but rather is dictated by the characteristics desired for the overall composition. Thus, in certain applications there may be a greater need for low toxicity, indicating a higher percent of 2-Chloro-1,1,1,2-tetrafluoroethane. In other instances, the emphasis may be on high efficacy, and less 2-Chloro-1,1,1,2-tetrafluoroethane may be desired. Therefore, no particular ratios of compounds are required. However, for certain applications, blends containing at least about 1% of 2-Chloro-1,1,1,2-tetrafluoroethane, and more particularly from about 5% to about 99% 2-Chloro-1,1,1,2-tetrafluoroethane, are desirable.

A particularly desirable aspect of the present invention is that the use of 2-Chloro-1,1,1,2-tetrafluoroethane, which has an extremely low ODP, permits the preparation of blends with other extinguishants that have a significantly lower ODP than the compounds have without the 2-Chloro-1,1,1,2-tetrafluoroethane. Thus, a feature of

-11-

the present invention is the preparation and use of blends having an overall ODP of less than about 1.0, and more preferably less than about 0.5.

Along these lines,

- 5 2-Chloro-1,1,1,2-tetrafluoroethane may be used as a partial replacement for halogenated hydrocarbons otherwise used in fire extinguishing compositions. In other words, for a composition including two or more of the prior art extinguishants,
- 10 2-Chloro-1,1,1,2-tetrafluoroethane may be used to partially or fully substitute for one of those compositions. This has the advantage of modifying the overall characteristics of the blend, such as by reducing ODP or toxicity. The
- 15 2-Chloro-1,1,1,2-tetrafluoroethane is therefore seen to be extremely flexible in its manner of use as a fire extinguishant.

The methods for application of the described fire extinguishing compositions are those known to be useful for similar halogenated hydrocarbons. In broad terms,

20 these methods utilize application systems which typically include a supply of agent, a means for releasing or propelling the agent from its container, and one or more discharge nozzles to apply the agent

25 into the hazard or directly onto the burning object. A system may also contain other elements, such as one or more detectors, remote and local alarms, a piping network, mechanical and electrical interlocks to shut down ventilation, etc., directional control valves,

30 etc. Such systems may be stationary or portable, and

-12-

typically the fire extinguishant may be pressurized with nitrogen or other inert gas at up to about 600 psig at ambient temperature.

Systems are broadly classified by their method of applying agent to the hazard. In total flooding systems, a sufficient quantity of extinguishing agent is discharged into an enclosure to provide a fire extinguishing concentration of agent throughout the enclosure. Total flooding systems are used, for example, for computer rooms, control rooms, special storage areas, machinery spaces and the like. Local application systems discharge fire extinguishing agent in such a manner that the burning object is surrounded locally by a high concentration of agent to extinguish the fire. Local systems are often employed because the enclosure may not be suitable to provide for total flooding. Examples include use for presses, tanks, spray booths, and electric transformers. Specialized systems are frequently used for specific applications or hazards, such as for aircraft, military vehicles, emergency generators, etc.

In the methods of the present invention, the level of usage is selected to give a fire extinguishing amount of fire extinguishant based on the particular composition chosen, the nature of the fire and burning material, the physical conditions surrounding the fire, etc. The methods may employ the fire extinguishing agents at essentially any concentrations at which fire may be extinguished, the exact minimum being dependent on factors such as the foregoing ones. A convenient

-13-

minimum level of usage is about 3% v/v. Preferred concentrations of the fire extinguishing composition are below about 15%, and more preferably from about 5% to about 10% v/v, although higher concentrations naturally will be effective.

The 2-Chloro-1,1,1,2-tetrafluoroethane, and other extinguishants if present, may be mixed with suitable propellants to facilitate application of the composition to a fire. Such propellants will include nitrogen, carbon tetrafluoride and CF_3H . Other compatible propellants or other compounds may also be mixed with the fire extinguishants of the present invention.

One of the notable advantages of 2-Chloro-1,1,1,2-tetrafluoroethane is the combination of efficacy, non-toxicity and low ODP. Prior art fire extinguishants typically are less desirable as to one or more of these properties.

2-Chloro-1,1,1,2-tetrafluoroethane is therefore a superior fire extinguishant in appropriate settings. By comparison, known extinguishants such as Halon 1301 and 1211 are more effective on a weight basis, but their ODP's are substantially higher than for 2-Chloro-1,1,1,2-tetrafluoroethane, rendering them environmentally unacceptable. The 2-Chloro-1,1,1,2-tetrafluoroethane compositions of the present invention have reduced ODP ratings, but are surprisingly effective at levels safe to humans, i.e. particularly at concentrations less than about 10%.

The invention will be further described with reference to the following specific Examples. However,

-14-

it will be understood that these Examples are illustrative and not restrictive in nature. In the following Examples, percents indicated are percents by weight unless indicated otherwise.

5

EXAMPLE 1

Dynamic flame extinguishing data for 2-Chloro-1,1,1,2-tetrafluoroethane were obtained using the cup burner test procedure with n-heptane as the fuel. Gaseous 2-Chloro-1,1,1,2-tetrafluoroethane was mixed with air and introduced to the flame, with the concentration of the agent being slowly increased until the flow was just sufficient to cause extinction of the flame. Data were also obtained in this manner for Halon 1301 (CF_3Br), Halon 1211 (CF_2BrCl), and CF_4 for comparative purposes. The percent of each agent added to air required to extinguish the flame is given in Table 1. As is apparent from these results, 2-Chloro-1,1,1,2-tetrafluoroethane has a much lower ODP at its extinguishing concentration than does CF_3Br or CF_2BrCl , even though the latter two required less concentration to extinguish the flame. The extinguishing concentration for each of these three compounds was well below 10% v/v. Although CF_4 has a zero ODP, the required extinguishing concentration was an unacceptable 16.5% v/v.

25

EXAMPLE 2

2-Chloro-1,1,1,2-tetrafluoroethane, Halon 1301, Halon 1211 and CF_4 were used to extinguish n-butane diffusion flames using the method of Example 1. Test data are reported in Table 2 and similar results as for Example 1 were obtained.

30

-15-

Table 1

Extinguishment of n-Heptane Diffusion Flames

Agent	Air Flow cc/min	Agent Required cc/min mg/L		Agent in Air, % added *	ODP
5					
CF ₃ CHFCl	16,200	1,166	400	7.2	0.018
CF ₃ Br	16,200	422	158	2.6	14.26
CF ₂ BrCl	16,200	437	182	2.7	2.64
CF ₄	16,200	2,668	593	16.5	0.00

10

Agent required mg/L = $\frac{\text{mg agent at extinguishment}}{\text{L Air}}$

Agent in air, % added = $\frac{\text{cc/min agent at extinguishment}}{\text{cc/min air}} \times 100$

15 ODP = calculation by Lawrence Livermore Research Laboratory
(ozone depletion potential)

Table 2

Extinguishment of n-Butane Diffusion Flames

Agent	Air Flow cc/min	Agent Required cc/min mg/L		Agent in Air, % added *	ODP
20					
CF ₃ CHFCl	14,500	911	350	6.3	0.018
CF ₃ Br	14,500	282	116	1.9	14.26
25					
CF ₂ BrCl	14,500	344	162	2.4	2.64
CF ₄	14,500	1,961	485	13.5	0.00

n-Butane flow = 100 cc/min

Agent required mg/L = $\frac{\text{mg agent}}{\text{L Air}}$

30 Agent in air, % added = $\frac{\text{cc/min agent at extinguishment}}{\text{cc/min air}} \times 100$

-16-

ODP = calculation by Lawrence Livermore Research Laboratory

EXAMPLE 3

Dynamic flame extinguishing data using the cup
burner method of Example 1 were obtained for various
mixtures of 2-Chloro-1,1,1,2-tetrafluoroethane and Halon
1301. Air and a mixture of the agents were continuously
supplied to an n-heptane diffusion flame produced in a
glass cup burner. For a given Freon 124 flow, the flow
of Halon 1301 was slowly increased until the flow was
just sufficient to cause extinction of the flame. The
experiment was repeated at various Freon 124 flow rates,
and the results are reported in Table 3.

EXAMPLES 4-7

Tables 4-7 report diffusion flame extinguishment
results obtained using the method of Example 3 for the
following agent mixtures:

Table 4 - Freon 124 and Halon 1211

Table 5 - Freon 124 and Halon 1201

Table 6 - Freon 124 and CF₃CHF₂CF₃

Table 7 - Freon 124 and CF₄

These Tables also contain ODP data for the blends,
calculated as the sum of the mole % of the agents
multiplied by the agents ODP. For example, a 50:50 mole
percent mixture of Freon 124 and Halon 1301 has a
calculated ODP of $(0.5 \times 0.018) + (0.5 \times 14.26) = 7.14$.

-17-

Table 3
Extinguishment of n-Heptane Diffusion Flames
CF₃CHFCl/CF₃Br Mixtures

5	CF ₃ CHFCl*	CF ₃ CHFCl	CF ₃ Br	Total	CF ₃ CHFCl	CF ₃ Br	Total	
	<u>mol%</u> <u>wt%</u>	<u>% added</u>	<u>% added</u>	<u>% added</u>	<u>mg/L</u>	<u>mg/L</u>	<u>mg/L</u>	<u>ODP</u>
	0	0	0	2.6	0	158	158	14.26
	36.0	34.0	1.1	2.0	63	122	185	9.13
10	62.5	60.3	2.4	3.9	136	89	225	5.36
	79.6	78.1	3.7	0.9	205	57	262	2.92
	90.4	89.5	4.9	0.5	271	32	303	1.38
	97.0	96.7	6.0	0.2	334	11	345	0.45
	100	100	7.2	0.0	400	0	400	0.018

15

$$\% \text{ added} = \frac{\text{cc/min agent at extinguishment}}{\text{cc/min air}} \times 100$$

$$\text{mg/L} = \frac{\text{mg agent at extinguishment}}{\text{L air}}$$

20

*remainder CF₃Br

25

30

-18-

Table 4
Extinguishment of n-Heptane Diffusion Flames
CF₃CHFCl/CF₂BrCl Mixtures.

5	CF ₃ CHFCl		CF ₃ CHFCl	CF ₂ BrCl	Total	CF ₃ CHFCl	CF ₂ BrCl	Total	ODP
	<u>mol%</u>	<u>wt%</u>	<u>% added</u>	<u>% added</u>	<u>% added</u>	<u>mg/L</u>	<u>mg/L</u>	<u>mg/L</u>	
	0	0	0	2.7	2.7	0	182	182	2.64
	33.9	29.7	1.1	2.2	3.3	63	149	212	1.75
10	58.8	54.1	2.4	1.7	4.1	136	115	251	1.10
	76.8	73.1	3.7	1.1	4.8	205	75	280	0.63
	91.7	90.0	4.9	0.4	5.3	271	30	301	0.24
	97.1	96.5	6.0	0.2	6.2	334	12	346	0.09
	100	100	7.2	0.0	7.2	400	0	400	0.018

15

Table 5
Extinguishment of n-Heptane Diffusion Flames
CF₃CHFCl/CF₂HBr Mixtures

20	CF ₃ CHFCl		CF ₃ CHFCl	CF ₂ HBr	Total	CF ₃ CHFCl	CF ₂ HBr	Total	ODP
	<u>mol%</u>	<u>wt%</u>	<u>% added</u>	<u>% added</u>	<u>% added</u>	<u>mg/L</u>	<u>mg/L</u>	<u>mg/L</u>	
	0	0	0	3.2	3.2	0	174	174	0.89
	29.0	29.7	1.1	2.8	3.9	63	149	212	0.64
25	56.8	57.7	2.4	1.9	4.3	136	99	235	0.39
	76.1	76.8	3.7	1.2	4.9	205	62	267	0.23
	84.1	84.6	4.9	0.9	5.8	271	50	321	0.16
	94.4	94.6	6.0	0.4	6.4	334	19	353	0.07
	100	100	7.2	0.0	7.2	400	0	400	0.018

30

-19-

Table 6
Extinguishment of n-Heptane Diffusion Flames
CF₃CHFCl/CF₃CHFClF₃ Mixtures

5	CF ₃ CHFCl	CF ₃ CHFCl	CF ₃ CHFClF ₃	Total	CF ₃ CHFCl	CF ₃ CHFClF ₃	Total	
	<u>mol%</u>	<u>wt%</u>	<u>% added</u>	<u>% added</u>	<u>mg/L</u>	<u>mg/L</u>	<u>mg/L</u>	<u>ODP</u>
	0	0	0	6.1	0	421	421	0.000
	22.3	18.7	1.1	4.0	63	274	337	0.004
10	42.6	37.3	2.4	3.3	136	228	364	0.008
	62.9	57.5	3.7	2.2	205	151	356	0.011
	80.7	77.0	4.9	1.2	271	81	352	0.015
	93.8	92.4	6.0	0.4	334	27	361	0.017
	100	100	7.2	0.0	400	0	400	0.018

15

Table 7
Extinguishment of n-Heptane Diffusion Flames
CF₃CHFCl/CF₄ Mixtures

20	CF ₃ CHFCl	CF ₃ CHFCl	CF ₄	Total	CF ₃ CHFCl	CF ₄	Total	
	<u>mol%</u>	<u>wt%</u>	<u>% added</u>	<u>% added</u>	<u>mg/L</u>	<u>mg/L</u>	<u>mg/L</u>	<u>ODP</u>
	0	0	0	17.2	0	619	619	0.000
	8.0	11.9	1.1	13.0	63	468	531	0.001
25	19.8	27.6	2.4	9.9	136	356	492	0.003
	32.7	42.9	3.7	7.6	205	273	478	0.006
	50.9	61.5	4.9	4.7	271	169	440	0.009
	78.8	85.2	6.0	1.6	334	58	392	0.014
	100	100	7.2	0.0	400	0	400	0.018

30

-20-

What is claimed is:

1. A method for extinguishing a fire which comprises the steps of:
 - 5 a. introducing to the fire a fire extinguishing concentration of an extinguishant composition including 2-Chloro-1,1,1,2-tetrafluoroethane; and
 - b. maintaining the concentration of the composition until the fire is extinguished.
- 10 2. The method of claim 1 in which step a. comprises introducing a concentration of the composition of less than about 15% (v/v).
3. The method of claim 2 in which step a. comprises introducing a concentration of the composition
- 15 of between about 3% and about 10% (v/v).
4. The method of claim 1 in which said introducing of step a. comprises introducing the composition through a total flooding system.
5. The method of claim 4 in which step a.
- 20 comprises introducing a concentration of the composition of less than about 15% (v/v).
6. The method of claim 1 in which said introducing of step a. comprises introducing the composition through a portable extinguishing system.
- 25 7. The method of claim 1 in which said composition consists essentially of 2-Chloro-1,1,1,2-tetrafluoroethane.
8. The method of claim 1 in which said composition consists essentially of
- 30 2-Chloro-1,1,1,2-tetrafluoroethane and a propellant.

-21-

9. The method of claim 1 in which said composition further includes at least a second halogenated hydrocarbon fire extinguishing agent.

10. The method of claim 9 in which said composition
5 further includes one or more additional fire
extinguishing agents selected from the group consisting
of bromodifluoromethane (CHF_2Br),
dibromodifluoromethane (CF_2Br_2),
bromotrifluoromethane (CF_3Br),
10 bromochlorodifluoromethane (CF_2BrCl),
chloropentafluoroethane ($\text{CF}_3\text{CF}_2\text{Cl}$),
dibromotetrafluoroethane ($\text{CF}_2\text{BrCF}_2\text{Br}$),
bromotetrafluoroethane (CF_3CHFBr), heptafluoropropane
($\text{CF}_3\text{CHFCF}_3$), 1,1,1,3,3,3-Hexafluoropropane
15 ($\text{CF}_3\text{CH}_2\text{CF}_3$), 1,1,1,2,3,3-Hexafluoropropane
($\text{CF}_3\text{CHFCHF}_2$), pentafluoroethane (CF_3CHF_2) and
mixtures thereof.

11. The method of claim 10 in which said
composition comprises a mixture of
20 2-Chloro-1,1,1,2-tetrafluoroethane and
bromodifluoromethane.

12. The method of claim 10 in which said
composition comprises a mixture of
2-Chloro-1,1,1,2-tetrafluoroethane and $\text{CF}_3\text{CHFCF}_3$.

25 13. In a fire extinguishing composition of
halogenated hydrocarbons, the improvement comprising
including from about 1% to about 99% of the compound
2-Chloro-1,1,1,2-tetrafluoroethane.

14. The improvement of claim 13 in which said
30 composition further includes one or more halogenated

-22-

hydrocarbons selected from the group consisting of
bromodifluoromethane (CHF_2Br), dibromodifluoromethane
(CF_2Br_2), bromotrifluoromethane (CF_3Br),
bromochlorodifluoromethane (CF_2BrCl),
5 chloropentafluoroethane ($\text{CF}_3\text{CF}_2\text{Cl}$),
dibromotetrafluoroethane ($\text{CF}_2\text{BrCF}_2\text{Br}$),
bromotetrafluoroethane (CF_3CHFBr), heptafluoropropane
($\text{CF}_3\text{CHFCF}_3$), 1,1,1,3,3,3-Hexafluoropropane
($\text{CF}_3\text{CH}_2\text{CF}_3$), 1,1,1,2,3,3-Hexafluoropropane
10 ($\text{CF}_3\text{CHFCHF}_2$), pentafluoroethane (CF_3CHF_2) and
mixtures thereof.

15 15. The improvement of claim 14 in which said
composition consists essentially of a mixture of
2-Chloro-1,1,1,2-tetrafluoroethane and
bromodifluoromethane.

16. The improvement of claim 15 in which said
composition comprises from about 5% to about 99%
2-Chloro-1,1,1,2-tetrafluoroethane and from about 95% to
about 1% bromodifluoromethane.

20 17. The improvement of claim 14 in which said
composition consists essentially of a mixture of
2-Chloro-1,1,1,2-tetrafluoroethane and $\text{CF}_3\text{CHFCF}_3$.

18. The improvement of claim 17 in which said
composition comprises from about 5% to about 99%
25 2-Chloro-1,1,1,2-tetrafluoroethane and from about 95% to
about 1% $\text{CF}_3\text{CHFCF}_3$.

19. The improvement of claim 14 and which further
includes an inert propellant.

INTERNATIONAL SEARCH REPORT

International Application No PCT/US 91/00999

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶ According to International Patent Classification (IPC) or to both National Classification and IPC IPC ⁵ : A 62 D 1/08														
II. FIELDS SEARCHED <div style="text-align: center; font-size: small;">Minimum Documentation Searched ⁷</div> <table style="width: 100%; border: none;"> <tr> <td style="width: 25%; border: none; vertical-align: top;">Classification System </td> <td style="border: none; vertical-align: top;">Classification Symbols</td> </tr> <tr> <td style="border: none; vertical-align: top;">IPC⁵ </td> <td style="border: none; vertical-align: top;">A 62 D</td> </tr> </table> <div style="text-align: center; font-size: x-small; margin-top: 5px;">Documentation Searched other than Minimum Documentation to the extent that such Documents are included in the Fields Searched ⁸</div>			Classification System	Classification Symbols	IPC ⁵	A 62 D								
Classification System	Classification Symbols													
IPC ⁵	A 62 D													
III. DOCUMENTS CONSIDERED TO BE RELEVANT ⁹ <table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <thead> <tr> <th style="width: 10%;">Category ⁹</th> <th style="width: 60%;">Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²</th> <th style="width: 30%;">Relevant to Claim No. ¹³</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; vertical-align: top;">P, X</td> <td>EP, A, 0383443 (I.C.I.) 22 August 1990 see the whole document ---</td> <td style="vertical-align: top;">1-11, 13-16, 19</td> </tr> <tr> <td style="text-align: center; vertical-align: top;">X</td> <td>US, A, 2021981 (F.R. BICHOWSKY) 26 November 1935 see page 1, left-hand column, line 41 - right-hand column, line 15 ---</td> <td style="vertical-align: top;">1, 7, 13</td> </tr> <tr> <td style="text-align: center; vertical-align: top;">A</td> <td>GB, A, 1368443 (I.C.I.) 25 September 1974 see page 1, lines 10-34; page 2, lines 4-46; example 2; table 2; claims -----</td> <td style="vertical-align: top;">1-10</td> </tr> </tbody> </table>			Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³	P, X	EP, A, 0383443 (I.C.I.) 22 August 1990 see the whole document ---	1-11, 13-16, 19	X	US, A, 2021981 (F.R. BICHOWSKY) 26 November 1935 see page 1, left-hand column, line 41 - right-hand column, line 15 ---	1, 7, 13	A	GB, A, 1368443 (I.C.I.) 25 September 1974 see page 1, lines 10-34; page 2, lines 4-46; example 2; table 2; claims -----	1-10
Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³												
P, X	EP, A, 0383443 (I.C.I.) 22 August 1990 see the whole document ---	1-11, 13-16, 19												
X	US, A, 2021981 (F.R. BICHOWSKY) 26 November 1935 see page 1, left-hand column, line 41 - right-hand column, line 15 ---	1, 7, 13												
A	GB, A, 1368443 (I.C.I.) 25 September 1974 see page 1, lines 10-34; page 2, lines 4-46; example 2; table 2; claims -----	1-10												
<div style="display: flex; justify-content: space-between; font-size: x-small;"> <div style="width: 45%;"> <p>* Special categories of cited documents: ¹⁴</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"a" document member of the same patent family</p> </div> </div>														
IV. CERTIFICATION <table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <tr> <td style="width: 50%; vertical-align: top;"> Date of the Actual Completion of the International Search 21st May 1991 International Searching Authority EUROPEAN PATENT OFFICE </td> <td style="width: 50%; vertical-align: top;"> Date of Mailing of this International Search Report 25. 06. 91 Signature of Authorized Officer miss T. MORTENSEN </td> </tr> </table>			Date of the Actual Completion of the International Search 21st May 1991 International Searching Authority EUROPEAN PATENT OFFICE	Date of Mailing of this International Search Report 25. 06. 91 Signature of Authorized Officer miss T. MORTENSEN										
Date of the Actual Completion of the International Search 21st May 1991 International Searching Authority EUROPEAN PATENT OFFICE	Date of Mailing of this International Search Report 25. 06. 91 Signature of Authorized Officer miss T. MORTENSEN													

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

US 9100999
SA 44893

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on 17/06/91
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A- 0383443	22-08-90	AU-A- 4902690	23-08-90
US-A- 2021981		None	
GB-A- 1368443	25-09-74	None	

EPO FORM P0079

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82